

DECLARATION OF PERFORMANCE

Date of issue: 2017-05-12
Replaces: No --- of: dd/mm/yyyy

DoP 2017-010

1	Unique identification of the product-type: PROMASTOP®-MG III	
2	Type of product: Masonry mortar (G)	
3	Intended uses : Masonry mortar for use in walls, pillars and partitions made of masonry (interior and exterior) after suitability test, which are subject to stability requirements.	
4	Name and contact address of the manufacturer: Promat International NV Bormstraat 24 B-2380 Tisselt Belgium Plant :26 www.promat-international.com	
5	System or systems of Assessment and Verification of Constancy of Performance (AVCP): System 2+	
6	Notified product certification body: Bayerischer Baustoffüberwachungs- und Zertifizierungsverein -BAYBÜV- e.V., Beethovenstraße 8, 80336 München 1497-CPR has issued the certificate of conformity of the factory production control based on the initial factory audit and the factory production control and carries out the ongoing monitoring, valuation and evaluation according system 2+.	
7	Declared performance	
	Essential characteristics	Performance
	Compressive strength	M10
	Composite strength	Characteristic initial shear strength (adhesive shear strength) tested according to EN 1052-3 method B in comparison with lime sand stone as reference at a moisture content of 3 to 6 M.-%: $\geq 0.10 \text{ N/mm}^2$
	Chloride content	$\leq 0.1 \text{ M.-%}$
	Reaction to fire	Class A1
	Water absorption	NPA
	Water vapor permeability	15/35 (table value)
	Thermal conductivity (table value)	$\lambda_{10,\text{dry,mat}} \leq 0.82 \text{ W/(m.k)}$ for P=50% $\lambda_{10,\text{dry,mat}} \leq 0.89 \text{ W/(m.k)}$ for P=90%
	Durability (frost resistance)	Based on the experience available the product is applicable for strongly attacking environments when applied appropriately according EN 998-2 Part B
	Dangerous substances	NPA
		Harmonised technical specification EN 998-2:2017

The performance of the product identified in this declaration of performance is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Bettina Rothböck
Function: Product Manager
Linz, 2017-05-12
Signature:

